

Disclaimer: Drawings produced by DANOSA UK should be considered non-scalable and for illustrative purposes only. Issued design principals form instructions for the installation of DANOSA UK materials only and should be considered as part of an overall design rather than in isolation. Product 'Technical Datasheets' are available for all DANOSA UK products and should be consulted in conjunction with all issued DANOSA UK installation instructions. Drawings are subject to copyright and should not be reproduced without permission.

**Drawing Notes:**  
 The structural substrates should be primed in accordance with the project specification. Substrates shown in this drawing are for illustrative purposes only.

Note A:  
 Where a full bond to the substrate is required, or where ESTERDAN 30 P ELAST SEMIADHESVIO is used as the underlay, GLASDAN 800 PERFORADO does not form part of the system.

Note B:  
 Drip card former to be mechanically fastened at 200mm centres. Alternatively, 2 staggered lines of roofing grade clout nails secured at 150mm centres on each staggered line.

Note C:  
 Fascia plate shown for illustrative purposes only. Vulnerable joint must be protected from wind-driven elements.

GLASDAN 800 PERFORADO  
 100mm Exclusion Zone

Drip Card Former  
 (see Note B)

DANOSA Capsheet  
 (as specification)

DANOSA Underlay  
 (as specification)

Minimum 50mm Cover  
 (past vulnerable joint)

Minimum 50mm Cover  
 (past vulnerable joint)

Drip Batten

Fascia Plate  
 (see Note C)

Air and Vapour Control Layer  
 (as specification)

GLASDAN 800 PERFORADO  
 (see Note A)

<b>Drawing Number:</b> DUK-B-(G)-220W	<b>Revision:</b> 00
<b>Date Drawn:</b> March 2017	<b>Author:</b> SL

Drawing Title:  
 Traditional Trim  
 Bituminous Membranes - Warm Roof



**DANOSA UK Limited**  
 Tel: 0845 074 0553 | www.danosa.co.uk | uktechnical@danosa.com