

Disclaimer: Drawings produced by DANOSA UK should be considered non-scalable and for illustrative purposes only. Issued design principals form instructions for the installation of DANOSA UK materials only and should be considered as part of an overall design rather than in isolation. Product 'Technical Datasheets' are available for all DANOSA UK products and should be consulted in conjunction with all issued DANOSA UK installation instructions. Drawings are subject to copyright and should not be reproduced without permission.

Drawing Notes:

All substrates should be primed with BITUMEN PRIMER HM. Structural substrates shown in this drawing are for illustrative purposes only.

Note A:
Paving slabs should be a minimum 50mm thick.

- Concrete Paving Slabs
(see Note A)
- DANOSA Paving Support Pads
- DANOFLOW
- DANOPREN XPS Insulation
(as specification)

- DURA-DAN ELAST 110/50 Elastomeric Liquid
(applied in a single application)
- DURA-DAN REINFORCEMENT MESH
(embedded in DURA-DAN ELAST 110/50 elastomeric liquid)
- POLYDAN 180-40/P ELAST+ HM
(or POLYDAN 180-40/P ELAST+ HM GARDEN where planting exists)



Building together

DANOSA UK Limited

Tel: 0845 074 0553 | www.danosa.co.uk | uktechnical@danosa.com

Drawing Number: DUK-D-(G)-202N	Revision: 00
Date Drawn: January 2019	Author: SL

Drawing Title:
Typical Cross Section with Paving Slabs on Paving Support Pads
DURA-DAN® Structural Hot Melt - Inverted