

Disclaimer: Drawings produced by DANOSA UK should be considered non-scalable and for illustrative purposes only. Issued design principals form instructions for the installation of DANOSA UK materials only and should be considered as part of an overall design rather than in isolation. Product 'Technical Datasheets' are available for all DANOSA UK products and should be consulted in conjunction with all issued DANOSA UK installation instructions. Drawings are subject to copyright and should not be reproduced without permission.

POLYDAN 180-40/P ELAST Capsheet
(or POLYDAN 50/GP ELAST+ GARDEN where planting exists)

DURA-DAN ELAST 110/50 Elastomeric Liquid

DANOPREN UPSTAND BOARD
(outlet hole carefully cut through facing)

POLYDAN 180-40/P ELAST+ HM
(or POLYDAN 180-40/P ELAST+ HM GARDEN where planting exists)

DURA-DAN REINFORCEMENT MESH
(embedded in DURA-DAN ELAST 110/50 elastomeric liquid)

JacBox Outlet Inspection Chamber

Leafguard & Clamping Grate
(see Note A)

DURA-DAN ELAST 110/50 Elastomeric Liquid
(applied in a single application)

DANOFLOW
(see Note B)

DANOPREN XPS Insulation
(as specification)

Drawing Notes:

All substrates should be primed with BITUMEN PRIMER HM. Structural substrates shown in this drawing are for illustrative purposes only.

20-40mm round washed stone covering shown for illustrative purposes only.

Parapet outlets should be cast into structural concrete substrates wherever possible. Where outlets are fitted to cored holes, the holes should ensure a snug and secure fit to prevent movement of the outlet (and spigot), and the outlet should be mechanically fastened to the structural deck.

Note A:
Parapet outlets should be supplied with a clamping grate to secure the waterproofing system and coupled with a suitable outlet guard as determined by the flow rate calculation.

Note B:
DANOFLOW should be turned down at rainwater outlets and drainage locations.

Important Note:
External finishes fall outside of DANOSA specification.

Drawing Number: DUK-D-(G)-301N	Revision: 00
Date Drawn: February 2019	Author: SL

Drawing Title:
Parapet Outlet
DURA-DAN® Structural Hot Melt - Inverted



Building together

DANOSA UK Limited

Tel: 0845 074 0553 | www.danosa.co.uk | uktechnical@danosa.com